


Manway Cover Detail



| | |
|--------------|---------|
| Inside Dia | 16 X 20 |
| No of bolts: | 1 |
| | |
| | |
| | |
| | |

Inner tank 7' 7-3/4" ID X 11' 9" seam to seam
Food / Dairy Grade

2-1/2" insulation inside full welded galvanized metal jacket .114" thick
Tank supports are 5" X 5" lugs with 4" sch 40 pipe socketed over 3" sch 40 pipe
Supports are 5' 8-1/2" center - to - center laterally

Description

Dimensions

| | | |
|--------------------------|-----------|-----------|
| O/A Length | A - | 12' 10" |
| Length - weld to weld | B - | 12' 2" |
| Diameter of Tank | O. D. C - | 8' 0-1/2" |
| Weld to End | D - | 9" |
| Width of Piers | E - | 5" |
| C/L of Piers to Weld end | F - | 1' 2-1/2" |
| C/L of Piers to Weld end | G - | 1' 2-1/2" |
| C/C of Piers | H - | 3' 7" |

Tank Openings

Tank Details

| No | Size | Type | Description | Tank Details | | Description | | Dimensions | |
|----|---------|-------|-------------------------------|---------------------|---------------|-------------------------------|-----------------|------------|--|
| 1 | 2-1/2" | SAN | Drain | Manufacturer: | UNKNOWN | Type of Head | Ellipse | | |
| 2 | 1" | NPT | Sight gauge lower | Date of manufacture | 1968 (est) | Tank Capacity | USWG | 5,000 | |
| 3 | 7" | Glass | (2) Sight glass 12" from cntr | Working Pressure | ATMOSPHERIC | Tank Weight | estimated | 6,000 | |
| 4 | 1" | NPT | Plugged | Steel Type: | 300 SERIES SS | Tank Shell (stainless inner) | 0.107 | | |
| 5 | 4-3/4" | SAN | Fill | | | Tank Head (stainless inner) | 0.105 | | |
| 6 | 4" | SAN | Fill | | | | | | |
| 7 | 2" | NPT | On Port # 6 | | | | | | |
| 8 | 16 X 20 | | Manway | | | | | | |
| 9 | | | | | | | | | |
| 10 | | | | | | Taken out of service 11/30/05 | | | |
| 11 | | | | | | | | | |
| 12 | | | | | | | | | |
| 13 | | | | | | | | | |
| 14 | | | | | | | | | |
| 15 | | | | | | Information taken by: | Gene B | | |
| 16 | | | | | | Date: | 11/6/2007 | | |
| 17 | | | | | | Tank Location | North Salem, NY | | |